



Todo lo que hacemos, lo tenemos hecho.

CAÑOS REDONDOS

TABLA DE PESO TEORICO EN KG. POR METRO

DIAMETRO		ESPESOR							
Pulg.	mm	0,8	0,9	1,25	1,6	2	2,5	3,2	4
5/8"	15,87	0,297	0,329	0,434	0,562				
3/4"	19,05	0,359	0,399	0,528	0,688				
7/8"	22,22	0,422	0,469	0,625	0,815				
1	25,4	0,485	0,539	0,72	0,94	1,15			
1 1/8	28,57	0,547	0,608	0,837	1,059	1,306			
1 1/4	31,75	0,61	0,678	0,934	1,184	1,462			
1 1/2	38,1	0,740	0,827	1,138	1,442	1,783	2,198	2,758	
1 3/4	44,44	0,870	0,968	1,333	1,693	2,097	2,590	3,260	
2	50,8	0,990	1,097	1,530	1,944	2,411	2,983	3,762	
2 1/4	57,15	1,115	1,250	1,726	2,195	2,724	3,375	4,264	
2 1/2	63,5			1,922	2,446	3,038	3,767	4,766	
3	76,2				2,948	3,665	4,551	5,770	
3 1/2	88,9				3,450	4,293	5,335	6,774	8,375
4	101,6				3,952	4,920	6,119	7,778	9,628
5	127					6,175	7,688	9,785	12,134
5 1/2	139,7						8,461	10,772	13,386
6	152,4							11,775	14,639

Comportamiento Físico

Fluencia (min.) 25kg/mm<sup>2</sup>  
Resistencia (min.) 35Kg/mm<sup>2</sup>